



Mobile High pressure cleaner, unheated FC 918 MP

► Data Sheet

MADE IN GERMANY

| | | | | |
|------------|--|-------------------------|-----------|------------|
| 1.0 | Type | FC 918 MP | | |
| 2.0 | Capacity | | | |
| 2.1 | Mains connection | 400 V 3 AC 50 Hz | | |
| 2.2 | Nominal consumption | 5,3 kW 9,5 A | | |
| 2.3 | Working pressure | 180 bar | | |
| 2.4 | Water - volume flow | 14,5 l/min | | |
| 2.5 | Operating temperature maximum | 70 °C | | |
| 3.0 | Specification | | | |
| 3.1 | High pressure pump with 3 solid ceramic plungers | Type NP 16/13 | Order nr. | 7041307000 |
| 3.2 | Unloader safety valve | Type VS - ULH 180 | Order nr. | 2098857000 |
| 3.3 | protects the high pressure system | | | |
| 3.4 | with injector 2,2 for the dosage of cleaning and preserving agents | | | |
| 3.5 | Duplex-spray lance for pressure regulation | | Order nr. | 2098290000 |
| 3.6 | with low pressure stage for the dosage of cleaning and preserving agents | | | |
| 3.7 | with rotating screw union | | Order nr. | 2085600000 |
| 3.8 | with mechanical spray gun | | Order nr. | 7041097000 |
| 3.9 | with high pressure flat jet nozzle | Type 25045 | Order nr. | 7027160000 |
| 3.10 | with low pressure flat jet nozzle | Type 4040 | Order nr. | 7025330000 |
| 3.11 | with high pressure hose 10 m | Type DN 8 | Order nr. | 2051560000 |
| 3.12 | Electrical motor for high pressure pump drive | Capacity 4 kW | Order nr. | 7040633000 |
| 3.13 | MP - Control "VarioStop" with cutoff delay | | | |
| 3.14 | Connecting cable 5 x 1,5 mm ² | 6 m with mains plug 16A | | |
| 4.0 | Dimensions with trolley (LxWxH) | 856x545x918 mm | | |
| 5.0 | Weight | 76 kg | | |

