



Mobile High pressure cleaner, oil-heated FH 711 TS

► Data Sheet

MADE IN GERMANY

1.0	Type	FH 711 TS	
2.0	Capacity		
2.1	Mains connection	230 V 1 AC 50 Hz	
2.2	Nominal consumption	2.9 kW 13 A	
3.0	High pressure stage		
3.1	Working pressure	115 bar	
3.2	Water - volume flow	11.5 l/min	
3.3	Operating temperature	90 °C	
4.0	Steam stage		
4.1	Working pressure	50 bar	
4.2	Water - volume flow	7.6 l/min	
4.3	Operating temperature	130 °C	
4.4	Oil atomizing burner	Typee LB 3	
4.5	Burner capacity	65 kW	
4.6	without flame control		
4.7	Burner nozzle	Typee 1.65/45°	
4.8	Fuel oil EL - consumption 7.2 l/h at constant operation with maximum operating temperature		
4.9	Flue gas temperature	180 °C	
4.10	Flue gas mass flow temperature	134 kg/h	
4.11	Flue gas volume flow	173 m³/h related to a flue gas temperature of 180 °C	
5.0	Specification		
5.1	High pressure pump with 3 solid ceramic plungers	Typee NP 10/11	Part no. 7041056000
5.2	Unloader safety valve	Typee UL with micro switch	Part no. 7041100000
5.3	Protects the high pressure system		
5.4	with turning handle for the setting of the operating stages high pressure/steam		
5.5	Dosage of cleaning and preserving agents selectively adjustable		
5.6	Spray lance		Part no. 7041098000
5.7	with mechanical spray gun		Part no. 7041097000
5.8	with high pressure flat jet nozzle	Typee 2505	Part no. 7023230000
5.9	with high pressure hose 10 m	Typee DN 8	Part no. 2098966000
5.10	Electrical motor for high pressure pump drive	Capacity 1.8 kW	Part no. 7041039000
5.11	Connecting cable 3 x 1.5 mm²	5 m with mains plug 16 A	
6.0	Dimensions with trolley (LxWxH)	1245x590x845 mm	
7.0	Weight	170 kg	



* EU declaration of conformity updated by the TÜV Hesse

subject to change without prior notice