


FRANK IVU 3.0 Automatic

Industrial Vacuum Unit



OSPREYFRANK
STEAM TECHNOLOGY




- ▶ Powerful industrial vacuum cleaner with liquid bath separator integrated in the dirt container
- ▶ Side channel blower for continuous operation
- ▶ Fully automatic control and regulation by SIEMENS PLC:
 - Water level sensor for water min.
 - Water level sensor for water max.
 - Temperature sensor for temp.max.
 - Fully automatic filling and emptying of the water tank.
 - Automatic steam cooling using network water
- ▶ Solenoid valve for network water
- ▶ Pump for automatic emptying of the water tank
- ▶ Stainless steel water tank
- ▶ Comfortable lowering of the water tank for easy disposal of the suction material.
- ▶ Mobile steel chassis, powder coated



MADE IN GERMANY

| Technical data FRANK IVU 3.0 | | Item No: 1309181 |
|-------------------------------------|------------------------|-------------------------|
| Power | 3.0 kW | |
| Tension | 400 / 50 Hz Volt | |
| Number of revolutions | 2,800 min-1 | |
| Admission | 6.8 A | |
| Protection | IP55 | |
| Negative pressure | 260 / 340 mbar max. | |
| Air flow | 330 m ³ /h | |
| SPL | 75 dB (A) | |
| Filter | 3 | |
| Filter surface | 3,000 cm ² | |
| Capacity | 100 lt. | |
| Dimensions | (HxWxD) 1700x630x835mm | |

Accessories **FRANK IVU 3.0**

| | |
|---|---|
|  | Suction hose DN 40 1307287 |
|  | Suction hose DN 50 1307288 |
|  | Suction hose DN 60 1307289 |

- PUR Suction hose
- with Wire spiral insert
- Electrically conductive
- Bending radius 64 mm

Technical changes and errors reserved